

MISP Training: Galaxies



CIRCL
Computer Incident
Response Center
Luxembourg



Team CIRCL

<http://www.misp-project.org/>
Twitter: @MISPPProject

MISP Training @ Helsinki
20180423

MISP Galaxies

- MISP started out as a platform for technical indicator sharing
- The need for a way to describe threat actors, tools and other commonalities became more and more pressing
- **Taxonomies quickly became essential for classifying events**
- The weakness of the tagging approach is that it's not very descriptive
- We needed a way to attach **more complex structures to data**
- Also, with the different naming conventions for the same "thing" attribution was a mess
- This is where the Galaxy concept came in

Solution

- Pre-crafted galaxy "clusters" via GitHub project
- Attach them to an event (or soon attribute)
- The main design principle was that these higher level informations are meant for human consumption
- This means flexibility - key value pairs, describe them dynamically
- Technical indicators remain strongly typed and validated, galaxies are loose key value lists

The galaxy object stack

- **Galaxy**: The type of data described (Threat actor, Tool, ...)
- **Cluster**: An individual instance of the galaxy (Sofacy, Turla, ...)
- **Element**: Key value pairs describing the cluster (Country: RU, Synonym: APT28, Fancy Bear)
- **Reference**: Referenced galaxy cluster (Such as a threat actor using a specific tool)

(some) Existing galaxies

- **Exploit-Kit:** An enumeration of known exploitation kits used by adversaries
- **Microsoft activity group:** Adversary groups as defined by Microsoft
- **Preventive measure:** Potential preventive measures against threats
- **Ransomware:** List of known ransomwares
- **TDS:** Traffic Direction System used by adversaries
- **Threat-Actor:** Known or estimated adversary groups
- **Tool:** Tools used by adversaries (from Malware to common tools)
- **MITRE ATT&CK:** Adversarial Tactics, Techniques, and Common Knowledge (ATT&CKTM)

What a cluster looks like

Galaxies

Threat Actor

- Sofacy   

Description

The Sofacy Group (also known as APT28, Pawn Storm, Fancy Bear and Sednit) is a cyber espionage group believed to have ties to the Russian government. Likely operating since 2007, the group is known to target government, military, and security organizations. It has been characterized as an advanced persistent threat.

Synonyms

APT28
APT28
Pawn Storm
Fancy Bear
Sednit
TsarTeam
TG-4127
Group-4127
STRONTIUM
Grey-Cloud

Source

MISP Project

Authors

Alexandre Dulaunoy
Florian Roth
Thomas Schreck
Timo Steffens
Various

Country



Refs

https://en.wikipedia.org/wiki/Sofacy_Group

Add new cluster

Attaching clusters to events

- Internally simply using a taxonomy-like tag to attach them to events
- Example: misp-galaxy:threat-actor="Sofacy"
- **Synchronisation works out of the box** with older instances too.
They will simply see the tags until they upgrade.
- Currently, as mentioned we rely on the community's contribution of galaxies

Attaching clusters

- Use a searchable synonym database to find what you're after



Creating your own galaxy

- Creating galaxy clusters has to be straightforward to get the community to contribute
- Building on the prior success of the taxonomies and warninglists
- Simple JSON format in similar fashion
- Just drop the JSON in the proper directory and let MISP ingest it
- We always look forward to contributions to our galaxies repository

Galaxy JSON

- If you want to create a completely new galaxy instead of enriching an existing one

```
1 {  
2     "name" : "Threat Actor",  
3     "type" : "threat-actor",  
4     "description": "Threat actors are characteristics of  
5         malicious actors (or adversaries) representing a cyber  
6         attack threat including presumed intent and  
7         historically observed behaviour.",  
8     "version": 1,  
9     "uuid": "698774c7-8022-42c4-917f-8d6e4f06ada3"  
10 }
```

Cluster JSON

- Clusters contain the meat of the data
- Skeleton structure as follows

```
1  {
2      "values": [
3          {
4              "meta": {},
5              "description": "",
6              "value": "",
7              "related_clusters": []
8          }
9      ]
10 }
```

Cluster JSON value example

```
1  {
2      "meta" : {
3          "synonyms" : [
4              "APT 28", "APT28", "Pawn Storm", "Fancy Bear",
5              "Sednit", "TsarTeam", "TG-4127", "Group-4127",
6              "STRONTIUM", "Grey-Cloud"
7          ],
8          "country" : "RU",
9          "refs" : [
10              "https://en.wikipedia.org/wiki/Sofacy_Group"
11          ]
12      },
13      "description" : "The Sofacy Group (also known as APT28,
14                      Pawn Storm, Fancy Bear and Sednit) is a cyber
15                      espionage group believed to have ties to the
16                      Russian government. Likely operating since 2007,
17                      the group is known to target government, military,
18                      and security organizations. It has been
19                      characterized as an advanced persistent threat.",
20      "value" : "Sofacy"
21  },
```

PyMISPGalaxies

```
from pymispgalaxies import Clusters
c = Clusters()
list(g.keys())
# ['threat-actor', 'ransomware', 'exploit-kit', 'tds', 'tool', 'rat', 'mitre-attack-pattern',
# 'mitre-tool', 'microsoft-activity-group', 'mitre-course-of-action', 'mitre-malware',
# 'mitre-intrusion-set', 'preventive-measure']
print(c.get("rat"))
# misp-galaxy:rat="Brat"
# misp-galaxy:rat="Loki RAT"
# misp-galaxy:rat="join.me"
# misp-galaxy:rat="Setro"
# misp-galaxy:rat="drat"
# misp-galaxy:rat="Plasma RAT"
# misp-galaxy:rat="NanoCore"
# misp-galaxy:rat="DarkTrack"
# misp-galaxy:rat="Theef"
# misp-galaxy:rat="Greame"
# misp-galaxy:rat="Nuclear RAT"
# misp-galaxy:rat="DameWare Mini Remote Control"
# misp-galaxy:rat="ProRat"
# misp-galaxy:rat="death"
# misp-galaxy:rat="Dark DDoSeR"
# ...
print(c.get("rat").description)
# remote administration tool or remote access tool (RAT), also called sometimes remote
# access trojan, is a piece of software or programming that allows a remote "operator"
# to control a system as if they have physical access to that system.
```

Q&A

- info@circl.lu (if you want to join the CIRCL MISP sharing community)
- OpenPGP fingerprint: 3B12 DCC2 82FA 2931 2F5B 709A 09E2 CD49 44E6 CBCD
- <https://github.com/MISP/> -
<http://www.misp-project.org/>
- We welcome any contributions to the project, be it pull requests, ideas, github issues,...